

Model:

RM-602 RING ROLLER

DIMAKIN

FEATURES:

- Very compact design
- Two driven rolls
- Manual top roll adjustment
- Standard segmental flat tooling
- Custom tooling available
- Lateral guide rolls
- Horizontal and vertical positions

**SPECIFICATIONS**

FLAT BAR (HARD WAY) ●●	60mm x 10mm Ø900mm
FLAT BAR (EASY WAY) ●●	80mm x 15mm Ø700mm
SOLID SQUARE ●●	35mm x 35mm Ø1000mm
SOLID ROUND ●●	Ø35mm Ø900mm
TUBE ●	Ø60mm x 2mm Ø1100
PIPE ●	Ø48.3mm x 2.9mm Ø1000mm
RECTANGULAR HOLLOW SECTION ●●	50mm x 40mm x 3mm
SQUARE HOLLOW SECTION ●●	40mm x 40mm x 3mm
ANGLE (TOE OUT) ●	50mm x 50mm x 5mm Ø800mm
ANGLE (TOE IN) ●	50mm x 50mm x 5mm Ø950mm
T-SECTION (TOE OUT) ●●	50mm x 5mm x Ø700mm
T-SECTION (TOE IN) ●●	50mm x 5mm x Ø900mm
T-SECTION (TOE UP) ●●	50mm x 5mm x Ø900mm
CHANNEL SECTION (TOES OUT) ●●	UPN 60 Ø900
CHANNEL SECTION (TOES IN) ●●	UPN 60 Ø1300
POWER	1.1kW 1.5hp
RPM	13.6/27.2
TOOL Ø	146/98
SHAFT Ø	50/50
SECTION MOD (CM3)	16
SHIPPING DIMENSIONS	300kgs 1000mm x 750mm x 1500mm

- Standard Rolls
- One set of rolls is required for each tube OD
- Special rolls for thin wall profiles
- Special profile